89


# **VA20**



COMPACT SIZE INTELLIGENT ASSET TRACKER

# Experience The Advantage

- COMPACT SIZE FOR CARGO MONITORING
- UNBOXING ALARM
- TEMPERATURE MONITORING
- HUMIDITY MONITORING
- DOOR SENSOR MONITORING
- VIOLENT TRANSPORTATION DETECTION



Featuring a wide range of positioning technologies, including GPS, Beidou, Wi-Fi, Bluetooth, and LBS, the VA20 ensures accurate and reliable tracking of your valuable assets. Whether they're on the move or stationed at a specific location, you'll have full visibility and control at your fingertips.

What sets the VA2O apart is its array of built-in sensors, designed to enhance functionality and deliver invaluable insights. Equipped with a light sensor, temperature sensor, humidity sensor, Hall sensor, and 3-axis/6-axis sensors, this tracker offers a comprehensive suite of features:

Unboxing Alarm, Temperature Monitoring, Humidity Monitoring, Door Sensor Monitoring, Violent Transportation Detection.

Additionally, the VA20 supports Bluetooth 5.0 communication, opening up a world of possibilities for various applications. Seamlessly connect and integrate with other devices and systems, expanding the capabilities and versatility of the VA20 to meet your specific needs.

# Vanguard

# GENERAL

Network Technologies	LTE-CAT 1 / GPRS / SMS
Location Technology	66 channel GPS
Operating Voltage	3.7V LiPo Battery

## **CELLULAR/BANDS**

4G LTE-FDD, EMEA VERSION	B1/B3/B5/B8	
4G LTE-FDD, LATIN VERSION	B2/B4/B8/B28	
GSM/GPRS	900/1800	

## GPS

GNSS	GPS, BDS
Receiver	66 channels
Location Accuracy	< 10 m
Tracking Sensitivity	-165 dBm
Acquisition Sensitivity	-148 dBm
Cold Start (open sky)	32 seconds
Hot Start (open sky)	1 second
AGPS / Location assistance capable	

#### POWER

Back-up battery	2500mAh / 3.7V LiPo battery	
Power Consumption	49 mA @ 3.7V working	
<2.5 mA @ 3.7V deep sleep		

#### **ENVIRONMENTAL**

Operating temperature	-20°C to +70°C	
Operating humidity	5% to 95% non-condensing	
Ingress Protection Rating	IP 65	

#### PHYSICAL

Dimensions	112.5 (L) x 62.0(W) x 11.0(H) mm
Weight	86 g



# SENSORS

Light sensor	support	
Accelerometer	Support	
Gyro	optional	
Hall sensor	Optional	
Temperature sensor	-40°C - +125°C ±0.3°C precision 0.1°C	
Humidity sensor	0-99% RH precision 0.1 ±5%	

## **INDICATORS**

Battery power	support	
Real-time positioning mode	support	
Cargo monitoring mode	support	
Long standby mode	support	
Temperature and humidity	support	

# BLUETOOTH

Bluetooth 5.0

support

Copyright © 2023, Vanguard IoT. Specifications and information given in this document are subject to change by Vanguard without prior notice.

Vanguard IoT Co., Ltd. | www.vanguardiot.com | info@vanguardiot.com